

## INSTRUCTION MANUAL for Sex Doll

### 1. Product Introduction:

- The outer layer of this product is manufactured by the new polymer material TPE (thermoplastic elastomer), the inner layer is constructed by epoxy resin and various metal joints, the product material conforms to the relevant safety standards stipulated by the state, no poison to the human body, the environment, please rest assured to use.
- Doll's body is equipped with each joint inside, can be placed in a certain range of postures, but because the product is factory for the straight posture, so can not be long-term doll placement difficult bending posture, so as not to make some glue due to long-term pull and deformation damage Arms and thighs can not be opened for a long time large arc, after use must be restored, let the doll lie flat and hands hanging on both sides of the body (non-standing solid dolls remember not to let the doll stand), such as improper use caused doll damage manufacturers will not bear.
- The body in the production of fixed internal bone joints, in the soles of the feet and thighs, hips, shoulder screws fixed holes, after treatment there are slight modifications, is an inevitable normal phenomenon.

### 2. Note:

- Can not use sharp apparatus scratching skin surface, can not pinch hard to avoid damage to the skin, affecting the use of time and beautiful.
- Dolls wear clothing, should avoid wearing easy to color or poor coloring technology clothing, so as not to pollute the doll's skin, affect aesthetics.
- The doll can not be placed in direct sunlight environment for a long time, so as not to cause the deterioration of the glue, affecting the use of time.

### 3. Maintenance instructions:

- (What about indentations?) If there are indentations on the surface of the doll due to prolonged compression, you can use a hot towel to heat its parts for a period of time.
- (How do I clean up the doll when it's dirty?) If the surface area of the doll has dust and contaminants, you can use general lotion or makeup remover oil can be cleaned, such as laundry detergent, shower gel, etc., but should avoid the use of fingernails to scratch the skin surface. Wash the doll and other surface moisture dry, the distribution of the feel powder (can also be replaced by ordinary hazelnut powder) evenly applied to the surface of the doll's body, can make the doll's skin surface smooth as early as the beginning, delicate feel. Manufacturers suggest: according to the situation to do regular cleaning, maintenance.

- (What if I find a crack or a crack somewhere in the doll?) If the surface of the doll appears small area damage, you can use repair glue glue glue, first wash the damaged surface clean, the adhesive at the wound back to its original position, and then evenly apply a layer of glue, wait half an hour or so after dry solid can be. If there are other technical problems can be directly contacted with the seller or manufacturers, manufacturers as appropriate to provide processing technology.
- (How do I use patches?) The principle of patching agent (glue) is in the repair process to first break around the two sides of the glue melt (harmless to human beings, please rest assured to use), and then let the two sides around the break re-fused together, in normal circumstances will not affect the beauty after the break repair, but in the course of operation due to the patch glue after the break did not close, do not wipe the patch, with wet cloth or water wash and then wipe the patch, Otherwise, in the absence of cleaning up the broken mouth to continue to wipe the patch but break the mouth because of melting glue so that the break around the sides of the melting more and more serious.
- (What if the doll is dyed?) The use of specially designed TPE thermoplastic elastomer staining decoloring paste, efficient, convenient, fast, non-toxic, can remove local staining over a period of time, the use of the following methods:

#### 4. Next informations:

- According to the degree of dyeing size, cotton swabs with the right amount of ointment, uniform application in the stained part.
- After applying, place the dyeing part for a period of time will naturally fade, and then rub again every 4 hours, until removed. Depending on the depth of staining, the time of fading is determined, and small area staining usually completes fading within 24 hours. Severe staining is usually removed in 3-4 days. (Decoloring paste can only slow down decoloring to varying degrees, dyeing slightly can be removed, staining serious, can slow down some, can not be completely removed)
- Warm tip: This product is certified safe and non-toxic.

